MY23 OUTLANDER X MR 650



HIGHLIGHTS

- Rotax® snorkeled V-Twin engine with relocated CVT intake and outlet
- Relocated radiator
- Tri-Mode Dynamic Power Steering (DPS)
- Visco-4Lok front differential
- 12 in. (30.5 cm) cast-aluminum wheels
- 28 in. (71.1 cm) ITP Mega Mayhem† tires
- · Heavy-duty front bumper
- 3,500-lb (1,588 kg) winch
- Mud-riding footrests
- X-package coloration, graphics and seat cover

ENGINE	
Туре	44 kW (59 hp), Rotax® 650 cc V-twin, snorkeled, liquid cooled with relocated radiator
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI)
Rear Shocks	Oil
TIRES / WHEELS	
Front Tires	ITP† Mega Mayhem 28 x 8 x 12 in. (71.1 x 20.3 x 30.5 cm)
Rear Tires	ITP† Mega Mayhem 28 x 10 x 12 in. (71.1 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum
BRAKES	
Front	Dual 214 mm diag brakes with hydraulia
FIONE	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	913 lb (414 kg)
LxWxH	88 x 48.5 x 50.5 in.
	(224 x 123 x 128 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	11.75 in. (29.9 cm)
Seat Height	35.25 in. (89.5 cm)
Rack Capacity	Rear: 200 lb (90 kg)
Storage Capacity	5.7 gal (21.4 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES

Gauge	4.5 in. digital display
nstrumentation	DC Outlet,15-A connector
ngnition	RF Digitally Encoded Security System (D.E.S.S.™)
ighting	LED headlights
Vinch	3,500-lb (1,588 kg) winch
Seat	Standard
landlebar	Standard
Protection	Heavy-duty front bumper
	Mud-riding footrests
	Mudguards

WARRANTY



